		F 27	
1	CATHODE RAY TUBE CIRCUITS	5.37	Device has particular grid
3	.Combined cathode ray tube and	F 20	structure
	circuit element structure	5.38	With particular collector or
3.5	Traveling wave tube with delay-		anode structure
	type transmission line	5.39	Plural hollow devices
3.6	Line with plural	5.41	Accelerating or decelerating
	characteristics or plural		the ray between the hollow
	lines		devices
4	Inductor or distributed	5.42	Devices excited to
	parameter-type inductive		accelerate the ray across
	structure		their gaps; e.g., synchrotrons
5	Ray passes in or through a	5.43	Devices of different
	hollow distributed parameter		resonance frequency
	device	5.44	Feedback connection between
5.11	With a secondary emission		the hollow devices
	stage	5.45	Three hollow devices
5.12	Secondary emission passes	5.46	Device tunable
	through or in the hollow	5.47	Gang tuned hollow devices
	device	5.48	Device has a flexible wall
5.13	With a magnetron	5.49	Three hollow devices
5.14	Plural rays pass through or	5.51	Plural gaps in the hollow
	in the hollow device		device
5.15	Rays merged at the hollow	5.52	Device has a re-entrant
	device		portion surrounding the ray
5.16	Plural hollow devices	5.53	Device tunable
5.17	Feedback by ray	5.54	Device has a flexible wall
5.18	Ray returns to the hollow	7	Connected to the deflecting
3.10	device; e.g., reflex type		electrodes
5.19	By same path and/or to same	8	.Compensating for stray
3.13	aperture	O	deflecting fields
5.21	Device tunable	8.51	.Pulse storing
5.22	Device tunable	8.61	Plural cathode-ray tubes or
5.23	Thermally controlled	0.01	ray-type tubes
5.24	<u>-</u>	9	.Plural cathode-ray tubes in the
5.24	Deflecting or reflecting the	,	circuit
E 0E	ray	10	.With radiant energy sensitive
5.25	Ray sweeps over an aperture	10	control means
F 26	or slot in the hollow device	11	With secondary emission stage
5.26	Device deflects the ray	11	in the cathode-ray tube
5.27	Plural hollow devices	11.5	Color convergence controlled
5.28	Plural hollow devices	11.5	by photodetector
5.29	Ray has appreciable	10 1	
	transverse electrical	12.1	.With secondary emission stage in
	dimension and/or significant	12 1	the cathode-ray tube
E 04	shape	13.1	.Plural ray-type tube
5.31	Hollow ray	13.11	Storage tubes
5.32	Disk-shaped ray	14	.Plural concentrating,
5.33	Device also a ray anode or		accelerating, and/or de-
- 0:	cathode	1 -	accelerating stages
5.34	Focusing and/or concentrating	15	Three or more stages
	the ray	16	Intermediate stage at lower
5.35	By magnetic field		potential
5.36	Device removable from its		
	grids		

17	With ray-deflecting stage interposed between plural	376	With post deflection phosphor selection
	concentrating or accelerating	377	With marker
	and/or de-accelerating stage	378	Circular, spiral, or radial
	or co-extensive with one such	370	sweeps
	stage	379	With additional control of
364	.Cathode-ray deflections circuits		cathode ray
365	Symbol generator	380	Control only at turn-on or
366	For flat cathode-ray tube		turnoff of circuit
368.11	Including color convergence control	381	Circuits control grid-cathode circuit of tube
368.12	Including specified signal	382	With focusing of ray
	storage (e.g., memory,	382.1	For television
	register, etc.)	383	Intensity control of ray
368.13	Interpolation	384	
368.15	Including electrostatic	385	Ray blanking
300.13	element (e.g., electrode,		Ray unblanking
	lens, etc.)	386	With ray control responsive
368.16	Offset apertures in plural		to deflection circuit
300.10	sequential electrodes	387	Including feedback circuit
260 17	-	388	Plural feedback circuits
368.17	Including signal delay	389	Negative feedback
260 10	circuitry	390	Tube-type circuit
368.18	Including specified waveform	391	Plural deflection circuits
0.50 1.0	generating circuitry	392	Plural waveform display
368.19	By nonlinear device (e.g.,		circuits
	square law device, diode,	393	Interconnected sweep circuits
	etc.)	394	Plural deflections in one
368.21	Parabolic waveform		plane
368.22	By integrating of signal	395	Plural potentials or currents
368.23	By multiplying of signal		applied to deflection member
368.24	Static convergence feature	396	Push-pull deflection circuit
368.25	Including core or winding	397	Coil-type circuit
	structure	398	With cathode-ray centering
368.26	Adjacent to or integral with	399	With Cathode-Tay CenteringDeflection coil circuit
	deflection winding or housing	400	Including a saturable element
	structure therefor		3
368.27	Including particular magnetic	401	Including a temperature
	field distribution	400	responsive element
368.28	Including plural cores or	402	Including a voltage dependent
	coils	400	resistor
367	Including a digital-to-analog	403	Including an amplifier
	device	404	Tube-type amplifier
369	Target controls deflection	405	With transformer connecting amplifier to coil
	circuit	406	With power recovery circuit
370	With ray deflection distortion	407	With diode or amplifier
	correction or reduction	10,	across coil
371	By modulation of deflection	408	Including solid-state switch
	waveform		
372	For cathode-ray tube having	409	Including a discharge device
	plural targets	410	With device discharging a
373	Targets radially about cathode	2.0	condenser
374	Targets in single plane	30	.Ray modulation
375	For plural phosphor target tube	411	.Power supply from deflection circuit source

500	HIGH ENERGY PARTICLE ACCELERATOR TUBE	40	.Electrode formed as inductive impedance
501	.Magnetic field acceleration means	41	.Inductive impedance connected between electrodes of a
502	Cyclotron		discharge device load
503	Synchrotron	42	Connected to plural anodes or
504	Betatron		plural cathodes
505	Linear accelerator (Linac)	43	Connected to control electrode
506	.Electrostatic accelerator means	44	With capacitive impedance
507	.With injection or extraction means		connected to the control electrode
32	COMBINED LOAD DEVICE OR LOAD	45	With diverse-type impedance
	DEVICE TEMPERATURE MODIFYING	46	.Filament, electric heater, or
	MEANS AND ELECTRICAL CIRCUIT DEVICE STRUCTURE		resistance in shunt with the discharge electrodes of a
33	.Portable self-contained		discharge device load
34	.With antenna	47	Automatic switch in the shunt
35	.Plural discharge device loads		circuit
36	Series connected discharge	48	Cathode or cathode heater in
	devices		the shunt circuit
37	Cathode-anode circuit connected to the discharge control electrode of another discharge	49	.Filament or electric heater in series with a discharge device load
	device load (e.g., cascade)	50	.Load device temperature-
38	Corresponding electrodes connected by a circuit		modifying means combined with or forming circuit impedance
	<pre>impedance (e.g., push-pull)</pre>	E 4	means
39	.Discharge device load with	51	.Plural circuit elements
	distributed parameter-type	52	Plural impedance elements
	transmission line (e.g., wave-	53	Diverse types of impedances
	guide, coaxial cable)	54	Plural inductive impedances
39.3	Traveling wave type with delay- type transmission line	55	.Electric generator or piezoelectric device
39.51	.Distributed parameter resonator-	56	.Discharge device load
	type magnetron	57	Discharge device and
39.53	With output-coupling means		transformer
39.55	Variable tuning	58	Discharge device and circuit
39.57	Electron emission type		impedance
39.59 39.61	Thermal or magnetic actuatorMovable tuning element (e.g.,	59	Impedance connected between two electrodes
	slug)	60	Impedance connected to an
39.63	With control electrode,		auxiliary starting electrode
	secondary emitter, or auxiliary anode or cathode	61	Discharge control discharge device
39.65	Having diverse size resonators	62	Inductive impedance
39.67	Tubular anode with eccentric or axially displaced cathode	63	Discharge control discharge load
39.69	With strapping for resonant	64	.Multiple filament load devices
39.71	structureMagnetic field generating and	65	Automatic substitution of the filament
	pole structure	66	Series connected filaments
39.73	Interdigital electrode	67	Diverse resistance filaments
39.75	Anode with plural cavities	68	Three or more controlled
39.77	With resonant cavity coupled to anode		filament circuits

69	Plural filaments energized in parallel	98	.Plural cathodes or heaters in the load device
70	.Load device and transformer	99	Series connected cathodes or
71			heaters
	.Load device and impedance	100	
72	.Load device and periodic electric switch	100	Thermostatic switch in the series circuit
73	.Electric switch inside evacuated	101	.Discharge device and/or
	or gas filled envelope		rectifier in the cathode or
74	.Automatic shunt circuit closing		heater circuit
	or cut-out switch	102	.Delayed application of the
75	Shunt circuit closing		discharge potential
76	SPECIAL APPLICATION	103	With surge generator in the
77	.Vehicle		discharge circuit
78	Vehicle motor or vehicle motion	104	Thermostatic controlled
70	driven generator	101	delaying means
7.0		105	.Pulsating or A.C. supply to the
79	Vehicle or engine speed	103	cathode or heater circuit
	controlled	100	
80	Load device controller combined	106	Automatic cut-out or voltage
	with vehicle controller		regulator in the cathode or
81	Steering mechanism controlled	4.00	heater circuit
82	Head light systems	107	.Automatic cut-out or voltage
83	Alternate circuit closing		regulator in the cathode or
84	.Door or closure controlled load		heater circuit
	device	108	CONFINED GAS OR VAPOR-TYPE LOAD
84.51	PULSE STORING SYSTEMS OF THE		DEVICE WITH PRESSURE
	GASEOUS DISCHARGE-TUBE TYPE		REGULATING MEANS
84.61	.With plural cathode or anode	109	.Auxiliary discharge type
	-	110	.Valve controlled
	tube	110	. vaive contitutied
85	tube WITH ELECTROMAGNETIC WAVE	111.01	DISCHARGE DEVICE LOAD WITH FLUENT
85	WITH ELECTROMAGNETIC WAVE		
85	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR		DISCHARGE DEVICE LOAD WITH FLUENT
	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS		DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE
85	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE	111.01	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE
86	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY	111.01	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply
	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode	111.01 111.11 111.21	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material
86 87	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution	111.01 111.11 111.21 111.31	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode
86	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE	111.01 111.11 111.21 111.31 111.41	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic field
86 87 88	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE	111.01 111.11 111.21 111.31 111.41 111.51	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction type
86 87	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load	111.01 111.11 111.21 111.31 111.41 111.51 111.61	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAcceleration
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment
86 87 88	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source .Gas ionization type (e.g., ion pump or gauge source)
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE
86 87 88 89 90	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source .Gas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE With tangential fluent material supply Plasma generating With extraction electrode With magnetic field DISCHARGE SPACE With tangential fluent material supply Plasma generating With extraction electrode With magnetic field DISCHARGE SPACE Gas induction type Gas ionization type USGAS ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER Plural load device systems
86 87 88 89 90	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load
86 87 88 89 90	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE With tangential fluent material supply Plasma generating With extraction electrode With magnetic field DISCHARGE SPACE With tangential fluent material supply Plasma generating With extraction electrode With magnetic field DISCHARGE SPACE Gas induction type Gas ionization type USGAS ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER Plural load device systems
86 87 88 89 90 91	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load
86 87 88 89 90 91 92 93	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices
86 87 88 89 90 91 92 93	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load
86 87 88 89 90 91 92 93 94	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load device
86 87 88 89 90 91 92 93 94	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systems	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage
86 87 88 89 90 91 92 93 94 95 96	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systemsSeries connected cathodes or heaters	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage regulator for the heater
86 87 88 89 90 91 92 93 94	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systemsSeries connected cathodes or	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115 116	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage regulator for the heater circuit

110		1 - 1	
118	.Load device circuit controlled	151	.Load device irradiating the
	by the temperature modifying		radiant energy responsive
	medium		device
119	WITH AUTOMATIC SHUNT AND/OR	152	.Plural load devices
	CUTOUT	153	Selective energization of the
120	.Combined with signal, indicator,		load devices
	or alarm	154	Selective electric switch
121	.Plural load device systems		controlled by the radiant
122	Series connected load devices		energy responsive device
123	.Plural shunts and/or cut-outs	155	.Plural radiant energy responsive
124	.Auxiliary electrode controlled		devices
125	.Shunt circuit closing	156	.Radiant energy control of an
126	With compensating impedance		electric discharge device in
127	.Supply circuit current and/or		the supply circuit of the load
	potential actuated switch		device
128	Plural switch operating means	157	.Discharge control discharge
129	WITH SIGNAL, INDICATOR, OR ALARM		device load controlled by the
130	.Plural load device systems		radiant energy responsive
131	Selective indication of the		device
	load device	158	.Radiant energy controlled
132	Plural signals, indicators, or		regulation of the current
	alarms		supply for the load device
133	.Plural signals, indicators, or	159	.Electric switch controlled by
	alarms		the radiant energy responsive
134	.Radiant energy responsive		device
	control type	160	PLURAL POWER SUPPLIES
135	.Discharge device and/or	161	.Plural load devices
	rectifier in the signal	162	Diverse type load devices
	circuit	163	Simultaneous application of
136	.Electrically operated switch		diverse type current supplies
	controlling the signal circuit		to a load device
137	POLYPHASE A.C. SUPPLY	164	Series connected current
138	.M phase to N phase (e.g., phase		supplies
	splitters)	165	Diverse type current supplies
139	Polyphase supply circuit	166	Simultaneous application to a
140	Phase multiplying		load device
141	.Transformer in the supply	167	.Plural cathode and/or anode load
	circuit		device
142	With interphase transformer in	168	Diverse type current supplies
	the supply circuit		to auxiliary and principal
143	Convertible transformer	1.50.1	electrodes
	connections	169.1	Diverse-type energizing or bias
144	Plural load devices		supplies to different
145	Plural cathode and/or anode	1.60.0	electrodes
	load device	169.2	Including shifting of
146	.Plural discharge control	1.60	register, counter, or display
	discharge device load devices	169.3	Electroluminescent device
147	.Plural cathode and/or anode	169.4	Gas display panel device
	discharge device load	170	.Series connected current
148	Discharge control discharge	1 7 1	supplies
	device	171	.Discharge device and/or
149	WITH RADIANT ENERGY SENSITIVE		rectifier in one of the supply
	CONTROL MEANS	170	circuits
150	.Radiant energy responsive load	172	.Periodic switch in one of the supply circuits
	device		suppry cricules

173	.Condenser in one of the supply	200 R	DISCHARGE DEVICE AND/OR RECTIFIER
4.7.4	circuits	0.04	IN THE SUPPLY CIRCUIT
174	.Plural diverse pulsating or A.C.	201 202	.Plural load device systems
175	supplies	202	.Plural cathode and/or anode discharge device load
176	.Diverse-type current suppliesSimultaneous application to the	203	Discharge device foad
170	load device	203	in the auxiliary starting
177	LOAD DEVICE IN THE PRIMARY AND		electrode circuit
1 / /	SECONDARY CIRCUIT OF THE	204	Discharge control discharge
	SUPPLY TRANSFORMER	201	device in the auxiliary
178	PLURAL DIVERSE-TYPE LOAD DEVICES		electrode circuit
179	.Series connected diverse-type	205	.Plural discharge devices and/or
	load devices		rectifiers in the supply
180	Plural diverse discharge device		circuit
	load	206	.Discharge device and/or
181	Asymmetrical discharge device		rectifier in the primary
	load		circuit of the supply
182	.Electric discharge device load	0.07	transformer
183	Plural diverse discharge device	207	.Discharge device and/or rectifier in shunt to the load
101	loads		device
184	THREE OR MORE LOAD DEVICES CONNECTED BETWEEN DIVERSE	208	.Discharge control discharge
	PAIRS OF PAIRED CONDUCTORS	200	device in the supply circuit
185 R	PLURAL SERIES CONNECTED LOAD	200 A	.Flashers
100 10	DEVICES	209 R	PERIODIC SWITCH IN THE SUPPLY
186	.Periodic switch in the supply		CIRCUIT
	circuit	210	.Plural load device systems
187	.Condenser in the supply circuit	211	Distributor type periodic
188	Condenser in shunt to load and	0.1.0	switch means
	supply	212	Transformer in the supply
189	.Discharge device loads	212	circuit
190	Asymmetrical discharge device	213	Distributor switch means in the primary circuits of plural
1 0 1	loads		transformers
191	.Convertible to parallel connected	214	With additional periodic
192	.Combined with parallel connected		switch in the primary circuit
172	load device	215	With additional periodic
193	.Electric switch controlled load		switch in the distributor
200	device		switch means circuit
185 S	.Christmas lights	216	Plural electrically operated
194	REGULATION OF THE CONTROL CURRENT		switches
	AND/OR POTENTIAL APPLIED TO	217	Periodic switch selectively
	DISCHARGE CONTROL DISCHARGE		connectable to plural load
	DEVICE LOADS BY PHASE SHIFTING	218	device circuits .Magnetoelectric generator supply
105	MEANS	219	.Periodic switch in the primary
195	.Plural load device systems	219	circuit of the supply
196	Inverse parallel connected asymmetric load devices		transformer
197	Discharge control discharge	220	Plural transformers in the
± , ,	device in the control circuit		supply circuit
198	Discharge control discharge	221	Secondary conductively
	device in the control circuit		connected to the primary
199	.Discharge control discharge	222	Plural interrupted transformer
	device in the control circuit		coil circuits

223	Condenser or inductance in the primary circuit	245	Resistance in the condenser
224	.Impedance or current regulator	227 A	.Arc machining
221	in the supply circuit	246	PULSATING OR A.C. SUPPLY
225	Periodic switch cut-out	247	.With power factor control device
226	.Plural periodic switches or	248	.Induction-type discharge device
220	multiple contact periodic	240	load
	switch	249	.Potential node-type discharge
209 Т	.Transistorized ignition systems	249	device load
209 CD	.Capacitor dischargeneous	250	.Plural load device systems
200 CD	ignition systems	251	Inverse parallel connected
209 M	.Miscellaneous ignition systems	251	-
			asymmetrical discharge device
209 PZ	.Piezoelectric ignition systems	0.50	loads
209 SC	.Silicon controlled rectifier	252	Discharge control discharge
005 -	ignition	0.50	device loads
227 R	CONDENSER IN THE SUPPLY CIRCUIT	253	Full wave systems with
228	.Plural load device systems		asymmetrical discharge device
229	Condenser connected to plural		loads
	cathodes or anodes of	254	Transformer in the supply
	asymmetrical discharge device		circuit
	loads	255	Plural transformers in the
230	Discharge control discharge		supply circuit
	device loads	256	Primaries in series
231	Plural series connected	257	With plural secondary or
	condenser and load device		tapped secondary
	circuits	258	Inductance in the supply
232	Condenser in shunt to load and		circuit
	supply	259	Variable inductance
233	.Plural cathode and/or anode	260	.Plural cathode and/or anode
	discharge device load		discharge device load
234	Condenser in the auxiliary	261	Auxiliary starting electrode-
	starting electrode circuit		type discharge device load
235	Condenser connected to plural	262	Transformer or auxiliary
	cathodes or anodes		winding in the auxiliary
236	.Electromagnetic influenced		electrode circuit
	discharge device load	263	Inductance or potential surge
237	.Discharge control discharge		generator in the auxiliary
	device load		electrode circuit
238	Condenser in the control	264	Impedance in the auxiliary
	circuit		electrode circuit
239	.Transformer in the condenser	265	Full wave-type system
	load device circuit	266	Transformer in the supply
240	.Electric switch in the condenser		circuit
	circuit	267	.Electromagnetic influenced
241 R	.Condenser in shunt to the load		discharge device load
	device and the supply	268	.Discharge control discharge
242	With an inductance in the		device load
	circuit	269	With plural discharge control
243	Inductance in series with the		devices
-	load device and the supply	270	Plural control potentials
241 P	Photoflash	271	Plural pulsating and/or A.C.
241 S	Strobe lights		potentials
244	.Inductance in the condenser	272	Rectifier and/or discharge
	circuit	_ / _	device in the control circuit
			13,100 III one concret cricuit

273	With condenser in the control	308	Regulator responsive to plural
	circuit		conditions
274	Transformer in the control	309	Thermal responsive regulator
	circuit	310	Shunted impedance-type
275	Condenser in the control		regulator
	circuit	311	Variable impedance-type
276	.Transformer in the supply		regulator
	circuit	312	PLURAL LOAD DEVICE SYSTEMS
277	Plural transformers in the	313	.Electric switch in the supply
	supply circuit		circuit
278	Three or more coil-type	314	Pre-selectable switching
	transformers		systems
279	Current regulator in the	315	Electrically controlled load
	primary circuit		device switch
280	Convertible to inductance	316	Keyboard or pattern controlled
281	Relatively movable core and		switch
	coil-type transformer	317	Three or more controlled load
282	Regulating transformer		device circuits
283	.Inductance in the supply circuit	318	Group control systems
284	Variable inductance	319	Four or more groups
285	Relatively movable core and	320	Plural switches
	coil-type inductance	321	Master circuit closing switch
286	Biased movable part with	322	Alternate circuit closing
	supply current controlled	323	.Sequential starting
	movement	324	.Plural discharge device loads
287	.Periodic-type current and/or	325	Discharge control discharge
	voltage regulator in the	323	device loads
	supply circuit	326	DISCHARGE DEVICE LOAD
288	supply circuit THREE OR MORE WIRE DISTRIBUTION	326 327	DISCHARGE DEVICE LOAD Discharge drawing-type discharge
288		326 327	DISCHARGE DEVICE LOAD .Discharge drawing-type discharge device
288 289	THREE OR MORE WIRE DISTRIBUTION		.Discharge drawing-type discharge device
	THREE OR MORE WIRE DISTRIBUTION SYSTEMS	327	.Discharge drawing-type discharge deviceTilting discharge device
	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN	327 328	.Discharge drawing-type discharge device
289	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT	327 328	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tilting
289	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the	327 328 329	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled
289	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit	327 328 329	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode type
289 290 291	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION	327 328 329 330	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode
289 290 291	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern	327 328 329 330	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting
289 290 291 292	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator	327 328 329 330 331	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the
289 290 291 292 293	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems	327 328 329 330 331	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrode
289 290 291 292 293 294	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation	327 328 329 330 331	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device
289 290 291 292 293 294	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuit
289 290 291 292 293 294 295	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the
289 290 291 292 293 294 295	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devices	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device
289 290 291 292 293 294 295 296 297	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulation	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit
289 290 291 292 293 294 295 296 297	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode
289 290 291 292 293 294 295 296 297 298	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators	327 328 329 330 331 332 333	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device load
289 290 291 292 293 294 295 296 297 298 299	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devices .Automatic regulation .Mechanically connected regulators .Plural regulators	327 328 329 330 331 332 333	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuitPlural cathode and/or anode discharge device loadAuxiliary starting electrode-
289 290 291 292 293 294 295 296 297 298 299 300	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devices .Automatic regulation .Mechanically connected regulators .Plural regulators .Current generator control	327 328 329 330 331 332 333 334 335	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrode-type discharge device
289 290 291 292 293 294 295 296 297 298 299 300 301	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulation .Mechanically connected regulators .Plural regulators .Current generator controlPlural automatic regulators	327 328 329 330 331 332 333 334 335	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuitPlural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting
289 290 291 292 293 294 295 296 297 298 299 300 301 302	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulatorsCurrent generator controlPlural automatic regulators .Current generator controlControl of the prime mover	327 328 329 330 331 332 333 334 335 336	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrode
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulators .Current generator controlPlural automatic regulators .Current generator control	327 328 329 330 331 332 333 334 335 336	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrode-type discharge devicePlural auxiliary starting electrodeDiverse potentials for the
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulatorsCurrent generator controlPlural automatic regulators .Current generator controlControl of the prime moverPlural field-type generatorThree or more fields	327 328 329 330 331 332 333 334 335 336 337	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuitPlural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrodeDiverse potentials for the discharge electrodes
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulatorsCurrent generator controlPlural automatic regulators .Current generator controlControl of the prime moverPlural field-type generator	327 328 329 330 331 332 333 334 335 336 337	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrode-type discharge devicePlural auxiliary starting electrodePlural auxiliary starting electrodeDiverse potentials for the discharge electrodesElectromagnetic influenced
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devices .Automatic regulation .Mechanically connected regulators .Plural regulators .Current generator control .Plural automatic regulators .Current generator controlControl of the prime moverPlural field-type generatorThree or more fields .Regulator in shunt to the load	327 328 329 330 331 332 333 334 335 336 337 338	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrodeDiverse potentials for the discharge electrodesElectromagnetic influenced discharge device

340	.With de-ionizing means in the cathode-anode circuit	DIG 1	FLUORESCENT LAMP CIRCUITS WITH MORE THAN TWO PRINCIPLE
341	.With plural discharge control		ELECTRODES
	devices	DIG 2	HIGH FREQUENCY STARTING OPERATION
342	Diverse types		FOR FLUORESCENT LAMP
343	Plural electromagnetic devices	DIG 3	CIRCUIT FOR ION GAUGES AND
344	.Electromagnetic influenced		PRESSURE GAUGES
	discharge device	DIG 4	DIMMING CIRCUIT FOR FLUORESCENT
345	Rail-type discharge device load		LAMPS
346	Plural current supply to the	DIG 5	STARTING AND OPERATING CIRCUIT
	electromagnet		FOR FLUORESCENT LAMP
347	Series connected with the load	DIG 7	STARTING AND CONTROL CIRCUITS FOR
	device		GAS DISCHARGE LAMP USING
348	Pulsating or A.C. supply to the		TRANSISTORS
	electromagnet		
349	.Discharge control discharge		
	device load		
350	Plural control currents and/or		
	potentials		
351	Plural pulsating or A.C.		
	currents and/or potentials		
352	Rectifier and/or discharge		
	device in the control circuit		
353	With condenser in the control		
	circuit		
354	Transformer in the control		
	circuit		
355	Condenser in the control		
	circuit		
356	Inductance in the control		
	circuit		
357	.Movable electrode discharge		
	device		
358	.Plural gases or vapors in the		
	discharge device		
359	PYRO-ELECTRIC DEVICE LOAD		
360	TIME-CONTROLLED		
361	PLURAL CONTROL STATIONS		
362	ELECTRIC SWITCH IN THE SUPPLY		
	CIRCUIT		
363	MISCELLANEOUS SYSTEMS		

FOREIGN ART COLLECTIONS

FOR 000 CLASS-RELATED FOREIGN DOCUMENTS

DIGESTS